



NOTE:

1.MATERIAL:

- a.HOUSING:PBT GLASS FIBRE
- b.CONTACT:PHOSPHOR BRONZE T=0.25mm (SURFACE PLATING: Au1u" + Sn100u" + Ni60u")
- c.SHEEL:BRASS T=0.30mm (SURFACE PLATING: Ni100u" ~ 120u")

2.ELECTRIC:

- a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c.DIELECTNIC VOLTAGE: 500V AC ONE SEC LEVEL
- d.OPERATING TEMPERATURE: -55??- 105??

RECOMMENDED P.C.B LAYOUT

未注公差	材质 MATERIAL	单位 UNIT	第三角投影	比例 SCALE	日期 DATE	品名	USB-AF沉板直边	
X	±0.1	mm		1 : 1 (A4)	08/09/17	图号	FCL-003	
X.X	±0.05	硬度 HRC	APPROVAL BY	CHECKED BY	DESIGNED BY	DRAWING	REV	
X.XX	±0.005		核准	审核	设计	绘图	版次	
X.XXX	±0.002						A	
							深圳市鑫南天科技有限公司	