


RECOMMENDED PCB LAYOUT(TOP VIEW) T=0.80mm
(GENERAL TOLERANCE ±0.05)



PRODUCT SPEC.
NOTES:

- 1).SPECIFICATIONS:
 - 1.1.VOLTAGE RATING:100V AC
 - 1.2.CURRENT RATING:1.0A
 - 1.3.INSULATION RESISTANCE:100 MEG.OHM MIN.
 - 1.4.CONTACT RESISTANCE:50 MILL.OHM MAX.
 - 1.5.OPERATION TEMPERATURE:-30 ° TO +80 °
 - 1.6.INSERT FORCE:35 N MAX.
 - 1.7.EXTRACT FORCE:8 N MIN.
 - 1.8.DURABILITY:10000 CYCLES

- 2).PLATING:
 - TERMINAL:
CONTACT AREA:GOLD FLASH,
SOLDER TAIL AREA:GOLD FLASH
UNDER PLATING:NICKEL 30u" Min.
 - SHELL:
MATTE TIN 80u" Min.
UNDER PLATING:NICKEL 30u" Min.

3	SHELL	STAINLESS STEEL	—	MATT TIN PLATED
2	TERMINAL	COPPER ALLOY	—	AU PLATED
1	HOUSING	HIGH TEMP	BLACK	UL 94V-0
NO.	DESCRIPTION	MAT.L	COLOR	REMARK

CUSTOMER COPY: 深圳市鑫南天科技有限公司
Shenzhen XinNanTian Industrial Co.,Ltd

TITLE: MICRO USB B REC.MID MOUNT THROUGH HOLE ASS'Y

PART NO. XNMTICR05PFXCB140PK

PRODUCT SPEC. XNMTICR05P00500

FILE NAME. XNMTICR05PFXCB140PK-C

SCALE 5:1 UNIT:mm A4 SHEET: 1 of 2

ECN NO.	REV	DATE	DESCRIPTION	CHANGE	APPRO.	Angle ±2° X ±0.35 .X ±0.25 .XX ±0.20	DESIGN COCO 12/17/12	
	A	12/17/12	NEW				CHECK JANY 12/17/12	
						GENERAL TOLERANCE UNLESS OTHERWISE NOTED	APPRO. JEFF 12/17/12	