

\* 所有原材料, 生产制程, 电镀必须符合ROHS要求

**一: 材质:**

- 1、胶壳: LCP, UL 94 V-0, 黑色
- 2、端子: 磷铜
- 3、外壳: 不锈钢

**二: 技术参数:**

接触电阻: 50 mΩMax  
 绝缘电流: 1000mA Min.(500V)  
 额定电压: 每个接触件1A Max  
 额定电压: 30V Max (DC)  
 耐压: 500V r.m.s/min  
 使用温度: -25℃~65℃  
 寿命: 5000次/MIN

**三: 电镀规格: 镀底30-50 U/min 全  
 部, 焊脚镀50 U/min, 接触点金**

Top view dimensions: 16.35, 15.00, 14.70, 14.05, 8.00, 3.43, 2.93, 1.75, 0.70, 14.70, 0.60.

Side view dimensions: 1.75, 1.50, 15.00.

Bottom view dimensions: 11.25, 0.80, 14.66, 0.35, 6.35, 1.40, 15.40.

Pin 1 location dimensions: 12.05, 9.60, 15.30, 13.30, 5.47, 1.27, 6.35, 4.23.

PIN NO	NAME	PIN NO	NAME
C1	VCC	C4	VPP
C2	GND	C5	CLK
C3	RST	C6	10

MICRO SIM

**■ SMT SOLDER AREA  
 RECOMMENDED PCB LAYOUT  
 GENERAL TOLERANCE ±0.05**

**UNLESS OTHERWISE SPECIFIED:**

DIMENSIONS INT: mm	TOLERANCE
X.X: ±	0.15
X.XX: ±	0.10
X.XX.X: ±	0.06
ANGULAR: ±	1°

REVISION NO.	DCR NO.	DESCRIPTION	DATE
1			
2			

**深圳市鑫南天科技有限公司**  
 Shen zhen Shi Xin Nan Tian Industrial Co., Ltd

PRODUCT NAME: MICRO-SIM 卡座标准式 1.80H	DRAWING: COCO	DATE: 2014/04/10
PRODUCT NO.: 0181AAA06A	CHECK: JANY	DATE: 2014/04/11
DRAWING NO.: XNT-0018	APPROVED: 林心祥	DATE: 2014/04/11
SCALE: 1:1	DWG ID: C.D	REV: A
		PAGES: 1 of 1