



REV	ECN NO	DESCRIPTION	DATE	NAME
A		NEW		

Specifications

- Current Rating: 3Amps
- Insulation Resistance: 1000 MΩ min.
- Dielectric withstanding Voltage: AC 550V
- Contact Resistance: 20 mΩ max.
- Operating Temperature: -55°C to +105°C
- Soldering Temperature: +265°C, 10s max
- Contact Material: Phosphor Bronze
- Insulation Material: NY6T 30% Glass Fiber Filled UL94V-0 Rated
- Plating: 1u" Min Au Plating Nickel Plated With 30u"-60u"

Ordering Information

L307 XX -XX 0 X XX XX X

- |         |       |        |          |          |      |
|---------|-------|--------|----------|----------|------|
| 塑胶高度H*W | PIN数  | 1、PBT  | 0、Au0.8" | 流水号      | A、袋装 |
| 5.0±2.6 | 1-40P | 2、     | 1、Au1"   | 01-69不带柱 | B、管装 |
| 5.7±2.4 |       | 3、NY6T | 2、Au1.5" | 70-99带内柱 | C、盘装 |
| 7.1±2.4 |       | 4、LCP  | 3、Au2"   |          | D、卷装 |
| 8.5±2.4 |       | 5、NY66 | 4、Au3"   |          |      |
|         |       | 6、     | 5、Au5"   |          |      |
|         |       | 7、NY46 | 6、Au10"  |          |      |
|         |       | 8、NY9T | 7、半盒锡    |          |      |
|         |       |        | 8、镀亮锡    |          |      |
|         |       |        | 9、镀雾锡    |          |      |

**XNT** 深圳市鑫南天科技有限公司  
Shenzhen XinNanTian Technology Co., Ltd

TOLERANCE UNLESS OTHERWISE SPECIFIED	TITLE	DRAWN BY	WZG	16.07.26
LINER ANGLES	PART NO	CHECKED BY		
0 ±0.30 0° ±3°	PH2.54X5.0 1X6P 180° 0.1mm 排母 U型	APPROVED BY		
.00 ±0.20 0° ±2°	DRAWING NO	PAGE	1/1	SIZE A4
.000 ±0.10 ±1°	SCALE 1:1	UNIT mm		